



## WINDING FRAME AND DEFLECTION YOKE

RECEIVED  
MAR 02 2004

### BACKGROUND OF THE INVENTION

#### Field of the Invention

5           The present invention relates to a deflection yoke. In particular, the present invention relates to the formation of a groove for adjusting the coiling density (or the quantity of the coil to be wound on a deflection coil) to a vertical direction at an arbitrary portion of an electric field on the  
10 internal side of the deflection coil in order to improve the coiling density of the deflection coil. Further, the present invention relates to the formation of a wire position guide on the inside of the winding frame of a winding machine that winds the deflection coil.

15           In other words, the present invention primarily aims to improve the characteristics of a deflection yoke in general by improving the constitution of a winding frame necessary for winding a deflection coil of a deflection yoke which consequently improves the properties of the deflection coil  
20 manufactured thereby.

#### Description of the Related Art

Figure 1 is a schematic cross-sectional view showing a construction of a general deflection yoke according to a  
25 related art. As shown in the drawing, the deflection yoke



the winding face.

The winding face 203 has a designated-shaped curved surface and inclination to wind the D-curve on the inside of the deflection coil of the deflection yoke. Thus, if the coil is wound, a deflection coil having the same shape as the winding face 203 is produced.

In addition, the guide face 204 formed on the both sides of the winding face 203 has a curved surface with a designated curvature, and is found along the direction of winding the coil. The guide face functions as a guide for entry of the coil by providing a back tension in an opposite direction of winding the coil.

Figure 3 is a perspective view of a winding face of a general A-type winding frame according to a related art. The A-type frame is operated through a guide pin hole 206 that projects on the winding face 203.

Moreover, the B-type frame (refer to 202 in Figure 2) is in gear with the A-type frame. As depicted in the drawing, unlike the A-type frame, the central portion of the B-type frame has a concave curved surface, called a winding face of the B-type frame.

The procedure of winding coil performed by the winding frames is now briefly explained. Once the winding frames are operated, the frames are rotated, and the coil wound around a bobbin (not shown) is uncoiled and instead, it flows in along

the guide face 204 of the A-type winding frame 201 to be wound around the winding face 203.

At the time, the guide face 204 provides a back tension in an opposite direction of the wound coil, consequently  
5 guiding the entry of the coil.

In short, the manufacturing process of a deflection coil of a deflection yoke using a winding machine composed of a traditional winding frame can be summarized as follows.

First of all, the winding task is performed on the  
10 winding face of the A-type and the B-type winding frames, where the A-type frame moves to the right and left while the B-type frame moves up and down. Also, a guide pin 205 undergoes reciprocation on the inside of the guide pin hole 206, through which the coil takes shape.

15 Afterwards, causing electricity to flow for the fusion (welding) finishes up the coil molding, and the coil is cooled down to harden the final shape of the coil as the way it is molded. Once the coil is molded, it goes through a bleed step.

20 In a so manufactured deflection coil, the coil is molded like the layered shape that is formed during the winding task between the D-curve on the inside and the F-curve on the outside. At this time, the coiling density varies depending on a cross section of the coil wound around  
25 the sectional area of the winding frame.

Figure 4 is a perspective view showing a part of the deflection coil that went through the manufacturing process described above.

Unfortunately however, when a general deflection coil  
5 is used for a deflection yoke, a phenomenon called mis-  
convergence occurs at the corner of the monitor screen, so  
the screen quality in general is deteriorated. In many cases,  
PQH(-) characters deteriorate said mis-convergence as well.

Figure 5 illustrates a poorly converged PQH(-). As shown in the drawing, R and B are not in accord with G (wherein, R is represented by a solid line, and B is represented by a dotted line).

The PQH is sometimes called CH. Apparently shown in the following mathematical equation I, as the PLM gets larger, 15 the mis-convergence occurs at the corner of the screen.

(Mathematical Equation I)

$$\text{PLM} = \text{PQH} - (\text{XH} + \text{YH}) .$$

wherein, XH and YH are horizontal errors at the x-axis and y-axis, or the corner, on the basis of G, given that R, G, and B are chrominance components manifested on the screen as shown in Figure 6.

Moreover, a phenomenon called S3V (+) shown in Figure 7 is also caused by the coiling density. Similar to before, Figure 7 illustrates the case in which R and B are not in  
25 accord with G (here again, R is represented by a solid line,

and B is represented by a dotted line).

Many attempts have been made to solve the problems with the traditional technique by altering a coiling number around the deflection yoke or through a local welding. In result, although the characteristic of a specific part was locally improved, the entire coiling density was changed thereby, which consequently failed to enhance the screen quality.

#### SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a winding frame and a deflection yoke for improving the constitution of a winding face of a winding frame by changing the coiling density on the inside of the deflection yoke by way of resolving a problem with mis-convergence.

In other words, the present invention is directed to enhancing overall characteristics of a deflection yoke by improving a deflection coil that is manufactured by using a winding frame with an improved constitution for winding a deflection coil of a deflection yoke.

To achieve the above object, there is provided a winding frame, which includes a winding face having a curvature of a designated-shape at the center, having mounted thereon a wire position guide that projects as much as a designated width in a vertical direction of a coil to be wound around an arbitrary portion of the internal electric

field for increasing coiling density; a guide face for guiding an entry of the coil, being disposed at both sides of the winding face with a curved surface and an inclination of a designated shape, and having mounted therein an internal  
5 guide pin for shaping a coil to be wounded around the winding face; and a base for supporting the winding face and the guide face, being fixed onto the guide face vertically.

Another preferred embodiment of the present invention provides a deflection yoke, which includes a conical coil  
10 separator having mounted thereon a front cover that bonds with a cathode-ray tube and a rear cover that bonds with the neck portion on the opposite end, a ferrite core for forming a magnetic field on the exterior of the coil separator, and a deflection coil for forming a magnetic field together with  
15 the ferrite core, in which a coiling density adjustment groove is formed in a vertical direction of the coil in order to increase the coiling density at an arbitrary portion of an electric field inside of the deflection coil.

Preferably, the wire position guide of the winding  
20 frame according to the present invention is disposed at approximately 1/2 of a longitudinal direction of the electric field.

Furthermore, the coil density adjustment groove of the deflection coil of the deflection yoke manufactured according  
25 to the present invention is also disposed at approximately





Figure 8 is a perspective view showing an A-type winding frame according to the present invention;

Figure 9 is a perspective view showing a winding face of the A-type winding frame according to the present  
5 invention;

Figure 10 is a perspective view showing a deflection coil according to the present invention; and

Figure 11 shows an improved screen by using a deflection yoke according to the present invention.

10

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A preferred embodiment of the present invention will now be described with reference to the accompanying drawings. In the following description, the same drawing reference  
15 numerals are used for the same elements even in different drawings. The matters defined in the description such as a detailed construction and elements of a circuit are simply ones provided to assist in a comprehensive understanding of the invention. Thus, it is apparent that the present  
20 invention can be carried out without those defined matters. Also, well-known functions or constructions are not described in detail since they would obscure the invention in unnecessary detail.

Figure 8 is a perspective view illustrating an A-type  
25 winding frame according to a preferred embodiment of the

present invention. As depicted in the drawing, there exists a winding face 3 with a curvature of a designated shape at the center of the winding frame. And, mounted on the winding face 3 is a wire position guide 7, which projects as much as  
5 a designated width in a vertical direction of the coil to be wound around an arbitrary portion of the inside of the electric field, in order to increase the coiling density of the coil to be wounded.

In addition, a guide face 4 having a curved surface and  
10 an inclination of a designated shape is formed on both sides of the winding face 3. On the other hand, there is a guide pin 5 mounted on the inside of the guide face, having a function of guiding an entry of the coil for the purpose of shaping the coil to be wounded around the winding face 3.

15 Figure 9 is a perspective view showing an important part of the A-type frame according to the present invention. Preferably, the wire position guide 7 projects approximately 1 to 3mm. However, this is adjustable at any time depending on the intensity of the magnetic field.

20 Figure 10 is a perspective view showing a part of a shape of the deflection coil bled from the winding frame for use of the deflection yoke according to the present invention. Being slightly different from the deflection coil in Figure 4, the deflection coil depicted in Figure 10 has a thin groove  
25 around the central portion of the inside of the coil ("B"

portion). This groove is called a coiling density adjustment groove.

Thusly constituted coil is then used for assembling a large planar type deflection yoke, enhancing particularly PQH  
5 and S3V characteristics out of other convergence characteristics on a screen. Figure 11 depicts the improved characteristics on the screen.

In conclusion, by improving the constitution of the winding face of the A-type winding frame of the deflection  
10 yoke coil winding machine according to the present invention, it is now possible to correct the mis-convergence and to enhance productivity and efficiency thereof.

While the invention has been shown and described with reference to certain preferred embodiments thereof, it will  
15 be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims.